



HAMILTON SAFE®



TABS

TACTICAL AWARENESS BEACON SYSTEMS

ShadowCash



ShadowCash is a state of the art cash tracking device.

ShadowCash is the solution to tracking and acquiring stolen bank cash. Shadow Cash's flexible design allows it to be used in a variety of tracking situations.

The primary components of Shadow Cash unit are advanced cellular and GPS connectivity chips matched with an extremely low profile board design. Cutting edge battery technology allows a low profile for factor as well as long periods between charges.

Shadow Cash fits nicely in a stack of cash, is flexible, and can be placed seamlessly in a cash drawer along side regular, non-tracking cash. For alternative situations the core unit can be fitted with a larger battery and a variety of sensors to fit customer needs.

Shadow Cash is complemented by (TrackSTing) Tactical Awareness Beacon Systems back end system, which tracks each Shadow Cash unit in real time. TrackSting also has a wide selection of alarms utilizing geo spatial tracking, and customizable sensors which can be integrated into Shadow Cash

Once a ShadowCash unit is activated, a signal gets sent to TrackSting. Bank security forces are alerted via an auditory alarm as well as a flashing red icon on an interactive map, allowing security to know where the unit is in the world with second by second updates.

Local authorities can then be given play by play updates of the criminals escape path, thus ensuring capture and the return of the cash.

TABS

TACTICAL AWARENESS BEACON SYSTEMS

www.tabscorp.com

Shadow Cash®

ACCURATE, FAST, LOW PROFILE, COST EFFECTIVE DEVICE FOR TRACKING STOLEN CASH

Battery Life Tracking	5hours on full charge. *
Battery Life Resting	7 months on full charge. *
Location Updates Tracking	Every 10 seconds
Service (Software)	T.A.B.S. TrackSting
Operating Temperature	-25 - 60° C / -13 - 140° F **
Network Interface	Cellular GSM, SMS, TCP/IP, UDP/IP
Sensors Available	Varied, customizable
Power Requirements	Battery or low voltage DC
Charging Method	On unit charging or battery replacement
Certifications	FCC, PTCRB, UL
Dimensions (L x W x H)	< 10.5 x 4 x 0.7 cm
Weight	< 60 grams *

* Battery life and dimensions/weight will vary based on model. Specifications for unit hidden in cash.

**Alternative battery technologies for cold weather use are available.

